

Technische gegevens

VIVAfloors

NL	EN	DU		Lijmversie	Clickversie
				20-05 (2,5 mm vloeren)	65-05(6,5 mm vloeren)
Product specificatie					
Totale dikte	Total Thickness	Gesamtstärke	EN 428	2,50 mm	6,5 mm
Dikte van de slijtlaag	Wear layer	Nutzschicht	EN 429	0,55 mm	0,55 mm
Dikte geluiddempende IXPE ondervloer	Thickness soundinsulating IXPE underlay	Stärke Trittschall IXPE Untergrund			1,5 mm
Totaal gewicht	Total Weight	Gesamtgewicht	EN 430	4 kg/m ²	7,2 kg/m ²
Toplaag	Surface treatment	Oberflächenvergütung	Embossed	PUR	PUR
Afmeting	Dimension	Abmessung		121,9 x 22,9 cm (5100-5800)	
				142,2 x 22,9 cm (4200/4300/ 6500/6800/8000)	142,0 x 22,5 cm (4200/4300/ 6500/6800/8000)
				45,7 x 91,4 cm (1610 - 1850)	45,7 x 93,5 cm (1610 - 1850)
				152,4 x 22,9 cm (7000)	152,4 x 22,9 cm (7000)
				15,24 x 60,96 cm (visgraat)	
Gebruikscategorie	Usage classification	Klassifizierung	EN 685	33-42	33-42
Test resultaten					
Vloerverwarming	Underfloor heating	Fussbodenheizung	EN12524	suitable max 27gr.	suitable max 27gr.
Warmte doorlaat weestand	Thermal resistance	Wärmedurchlasswiderstand	EN 12667	0,015 m ² K/W	0,068 m ² K/W
Rolstoeltest	Castor Chair	Rollstuhl	EN 425	pass	pass
Brandklasse	Fire resistance	Brandverhalten	EN 13501-1	Bfl-s1	Bfl-s1
Weerstand chemische stoffen	Chemical resistance	Chemikalienbeständigkeit	EN 423	Good	Good
Restindruk	Residual indentation	Eindruckverhalten	EN 433	<0,10mm	<0,10mm
Slijptest	Slip resistance	Rutschhemmung	EN 13893	Class DS (R9)	Class DS (R9)
Slijtage klasse	Abrasion class	Abriebklasse	EN 660-1	(volume loss)<2,0	(volume loss)<2,0
Geluidsabsorptie	Sound reduction	Reduzierung des Trittschalls	EN ISO 717-2	4 dB	17 dB Lw
Lichtechtheid	Light stability	Lichtechtheit	ISO 105-B02	pass 7 / 8	pass 7 / 8
Dimensionale stabiliteit	Dimensional stability	Massänderung	EN 434	<0,25%	pass
Afmeting	Dimension	Verlegemass	EN 427	pass	pass
Toxiteit	Toxic elements test	Toxizität	EN 71	niet giftig	niet giftig
Garantie		Garantie		Particulier / Residential 25 years	Particulier / Residential 25 years
				Projectmatig / Commercial 10 years	Projectmatig / Commercial 10 years

