

## Trouble-free wooden floors



A flooring with the Woodura® surface leaves you with much less worries. No more dents from high heels, toys or dropped objects, and no more wear marks from running pets or children's toys. With outstanding impact and wear resistance, these easily installed floors are suitable for virtually every room in a home or in commercial areas.

## **Awarded technology**







The Woodura® surface is based on fusing a thin sheet of wood with a wood fiber core through a powder mix layer. The powder mix perfectly fills up the natural openings of the wood and enhances the wood appearance. Moreover, it eliminates the need for putty operations and creates a significantly stronger surface with a hardness significantly greater than a traditional solid oak layer.

Brinell Hardness (HB)	<b>Oak</b> 3.7	Woodura 10.0
	Class 34 laminate	Woodura
Thickness swelling (%)	8.0	6.6
Impact resistance (Big ball)	≥ 1,600	≥ 1,600





# Give character to your room



Woodura® provides an opportunity to enhance the unique character of wood by combining different wood sheet qualities with powder mixes in different colors. After pressing, the flooring products with Woodura are treated with surface treatment, thereby adding further design possibilities that truly reflect one's individual taste.

Whether you want to give your room a contemporary, vintage or industrial character, a floor with Woodura can help you on the way.

## Make best use of nature



In addition to its technological advantages, Woodura® is also a sustainable way to bring real wood interior decoration into our homes. By using thin wood sheets instead of solid wood, 10 times more flooring can be produced from the same amount of lumber compared to traditional engineered wood flooring.











OULL1 | Wood: OAK | Base powder: NATURAL | Finish: NATURAL



OULL2 | Wood: OAK | Base powder: NATURAL | Finish: RAW



OULL3 | Wood: OAK | Base powder: NATURAL | Finish: WHITE



OULL5 | Wood: OAK | Base powder: NATURAL | Finish: DARK GREY



OULL6 | Wood: OAK | Base powder: RED/BROWN | Finish: BROWN



OULL7 | Wood: OAK | Base powder: RED/BROWN | Finish: DARK BROWN

### **Available formats**

NATURAL | Finish: GREY

Decor: 2379 x 276 mm | Deep matte UV-lacquer | Minibevel, 30° 0.3 mm | 1-strip (plank)

Thickness: 11 mm


Click system: 5G® Fold Down locking system

OULL4 | Wood: OAK | Base powder:

Decor: 2379 x 210 mm | Deep matte UV-lacquer | Minibevel, 30° 0.3 mm | 1-strip (plank)

Thickness: 11 mm

Click system: 5G® Fold Down locking system





OULO1 | Wood: OAK | Base powder: NATURAL | Finish: NATURAL



OULO2 | Wood: OAK | Base powder: NATURAL | Finish: RAW



OULO3 | Wood: OAK | Base powder: NATURAL | Finish: WHITE



OULO4 | Wood: OAK | Base powder: NATURAL | Finish: GREY



OULO5 | Wood: OAK | Base powder: NATURAL | Finish: DARK GREY



OULO6 | Wood: OAK | Base powder: RED/BROWN | Finish: BROWN



OULO7 | Wood: OAK | Base powder: RED/BROWN | Finish: DARK BROWN

### **Available formats**

Decor: 2379 x 276 mm | Hardwax oil | Minibevel, 30° 0.3 mm | 1-strip (plank)

Thickness: 11 mm

Click system: 5G® Fold Down locking system

Decor: 2379 x 210 mm | Hardwax oil | Minibevel, 30° 0.3 mm | 1-strip (plank)

Thickness: 11 mm

Click system: 5G® Fold Down locking system

## Product build-up

- 1. Hardwax oil or UV-lacquer
- 2. Real wood covering
- 3. Wood-based powder layer
- 4. High-quality moisture-resistant High Density Fiberboard
- 5. Wood-based powder layer
- 6. Wood veneer layer



## General & technical information



### REACTION TO FIRE

Standard: EN 13 501 Bfl-s1 (hardly flamable)



### FORMALDEHYDE EMISSIONS E1

Standard: EN 717-1 ≤ 0.05 ppm



### THERMAL CONDUCTIVITY

Suitable for hot-water underfloor heating. Standard foil heating systems are generally not recommended. (Exception: self-regulating heating systems which maintain a 26°C surface temperature).



### CLEANING

For removal of dirt and grime, it is recommended to clean the floors with the concentrate Wash and Care (8016) from Osmo.



### **CUTTING INSTRUCTIONS**

For cutting of the floor panels, hardened steel cutting tools or diamond-tipped sawblades are recommended.

### PRODUCT THICKNESS

11 mm

### WIDTH AND LENGTH

2379 X 210 mm | 2379 X 276 mm

### AREA OF APPLICATION

Woodura flooring products are suitable for all living areas as well as for commercial areas with normal wear, e.g. offices, waiting rooms, boutiques etc. The flooring is not suitable for installation in humid rooms (bathrooms, saunas etc.).

### INSTALLATION

The substrate must be dry, even, firm and clean. Any unevenness of 3 mm per 2 meter must be evened. The installation instructions provided with the product must be observed.

For detailed instructions, visit www.woodura.se

# woodura

## **Innovating Everyday**

Innovation has been the heart and soul of our business since the company was founded in 1993. Our progress is built on always challenging today's technological solutions with new ways of thinking. That's how we revolutionized the way people install and use floors. That's also the way we introduced a groundbreaking method to assemble furniture without any tools.

Today, our licensees can be found all over the world. All our development activities take place at our R&D center in Viken, Sweden. From here we develop new concepts and provide pilot manufacturing, testing and technical support.

Each day, we make sure our licensees get access to the latest flooring, furniture and surface technologies used in people's everyday lives.



Välinge Innovation AB www.valinge.se | www.woodura.com