# ntgrate® anti-slip

## Aqueous dispersion of an acrylic anti-slip glue

- anti-slip for Ntgrate carpet tiles
- · very low emission
- applicable on all load-bearing soils
- fast drying free of surfactants can not re-emulsified!
- slightly tinted

#### Substrate.

- The substrate must be pressure proof, strong, crack-free, permanently dry and free of dirt and separating agents.
- The substrate must have sufficient strength to intercept material stresses and dimensional changes that occur by laying materials and coverings.
- Any deficiencies should be reported to the contractor.

#### Processing.

- Ntgrate Anti-Slip is to be applied with a roller thinly and evenly, approx. 80-100 g/m².
- After complete drying the adhesive film will have just sufficient adhesion on the tile backing to allow easy lift up and re-installation and prevent lateral movement.
- Attention! Laying to fresh will cause a permanent bond.
- · Finger test: There must be no wetting.

#### Warning.

- This product is used for Ntgrate carpet tiles in accordance with EN 15114.
- The anti-slip glue only ensures that the textile floor covering to be laid is not easy to move horizontally.
- · Only apply dimensionally stable surfaces.
- For installation on raised floor avoid a penetration of glue in the seams of the raised floor tiles.

## Drying time.

• At least 30 minutes, to achieve a solid pressure-sensitive adhesive film.

## Consumption.

• 80-100 g/m<sup>2</sup>, applied with a roller

#### Working temperature.

• Min +15 ° C, R.H. should be less than 65 %

#### Storage Stability.

Up to 12 months, store frost-free.

#### Disposal.

- Only the completely emptied containers should be recycled.
- Cured material can be disposed of with household waste.

#### Notes.

- Keep out of reach of children.
- Provide thorough ventilation during application and drying.
- In case of contact with eyes or skin, immediately rinse thoroughly with water.
- Clean tools immediately after use with water and soap.
- Please pay attention to the valid technical information, the safety data sheet as well as to our delivery conditions and terms of payment